

**Copyright**

The interpretation right of this product specification belongs to BOE MLED. Without the signed permission of BOE MLED, any other individual or organization is not allowed, in any form, to excerpt, reproduce, copy, translate, edit or publish this product specification. This product specification is subject to modification without prior notice.



SPEC. NUMBER -	Product organization MLED	REV. -	Release date 2024.3.27	Page 1
-------------------	------------------------------	-----------	---------------------------	-----------

# **BKY015B Pre-Spec**

**Rev. 1**

**BOE MLED Technology Co., Ltd.**

### Copyright

The interpretation right of this product specification belongs to BOE MLED. Without the signed permission of BOE MLED, any other individual or organization is not allowed, in any form, to excerpt, reproduce, copy, translate, edit or publish this product specification. This product specification is subject to modification without prior notice.

# BOE

SPEC. NUMBER	Product organization	REV.	Release date	Page
-	MLED	-	2024.3.27	2

## 1. Product Introduction

### 1.1 Product Features

- Unit size 27", standard 16:9 display, can achieve 2K, 4K, 8K and above point-to-point splicing
- Adopt independent intelligent integrated control motherboard, no transmission design
- 2-channel HDMI input, support 2K@60HZ signal within the custom resolution, automatic positioning, no need to set up the alignment map
- 2-way HDMI output, support 2K@60HZ signal cascade
- Fine grayscale function, calibrate the grayscale step by step, optimize the grayscale jumping, colour deviation, pockmarks and other problems.
- 18/22bit, enhance the grey scale display effect, show more details
- Chroma space, support to adjust the display of standard colour gamut or custom colour gamut according to demand.
- Support brightness and chroma correction to ensure display consistency.
- Support FLASH management of light board
- Support fast seam repair
- Support RGB independent gamma adjustment
- Supports its own temperature and voltage monitoring function
- Support communication status real-time detection function
- Support Mapping function
- Support 3D effect display
- Support one key to read back all the configuration file information
- Unique colour change technology, make the human face skin tone more realistic
- Unique arbitrary frequency technology, mobile phone shooting without scan lines

## 2. Product Picture



## 3. Product Specification

Category	Parameters	Specification
Physical Parameters	Pixel pitch(mm)	1.56
	Pixel composition(RGB)	1
	Panel resolution(dots)	384*216
	Panel dimension(W × H × D)/(mm)	600*337.5*58
	Pixel density(dots/m <sup>2</sup> )	409600

**Copyright**

The interpretation right of this product specification belongs to BOE MLED. Without the signed permission of BOE MLED, any other individual or organization is not allowed, in any form, to excerpt, reproduce, copy, translate, edit or publish this product specification. This product specification is subject to modification without prior notice.

**BOE**

SPEC. NUMBER

Product organization

REV.

Release date

Page

-

MLED

-

2024.3.27

3

Category	Parameters	Specification
	Panel diagonal	27"
	Panel ratio	16:9
	Panel weight(Kg)	8
	Panel material	Die-casting Aluminum
Optical Parameters	Brightness(cd/m <sup>2</sup> )	0-650(Adjustable)
	Contrast ratio(Max.)	8000:1
	Color temperature(K)	2000-14000K
	Viewing angle horizontal/vertical	160° /160°
	Frame frequency(Hz)	50/60
	Refresh frequency(Hz)	3840
	Grayscale(bit)	16
	Driving mode	Constant drive
	AC operating voltage(V)	90-264
	Power maximum/average(W/m <sup>2</sup> )	450/140
	Input power frequency	50/60Hz
Application Parameters	Input signal	2-channel HDMI1.3(support conversion)
	Control system	Gridded four-way interconnection system with backup, standard HDMI interface, no need to set up, plug and play
	Storage temperature(°C)/Humidity(RH)	-10°C—+55°C/10—93%RH
	Storage temperature (°C)/Humidity(RH)	0°C—+45°C/10—93%
	Protection grade	IP50
	LED service time(H)	≥100,000
	Maintenance method	Front Maintenance

Note: The power is for reference only, the actual shall prevail.

#### 4. Plane Structure of the Product

Copyright

The interpretation right of this product specification belongs to BOE MLED. Without the signed permission of BOE MLED, any other individual or organization is not allowed, in any form, to excerpt, reproduce, copy, translate, edit or publish this product specification. This product specification is subject to modification without prior notice.

BOE

SPEC. NUMBER -	Product organization MLED	REV. -	Release date 2024.3.27	Page 4
-------------------	------------------------------	-----------	---------------------------	-----------

