

Copyright

The interpretation right of this product specification belongs to BOE MLED. Without the signed permission of BOE MLED, any other individual or organization is not allowed, in any form, to excerpt, reproduce, copy, translate, edit or publish this product specification. This product specification is subject to modification without prior notice.



SPEC. NUMBER -	Product organization MLED	REV. -	Release date 2023.11.30	Page 1
-------------------	------------------------------	-----------	----------------------------	-----------

BTS060

Product Introduction

Rev. 0

BOE MLED Technology Co., Ltd.

Copyright

The interpretation right of this product specification belongs to BOE MLED. Without the signed permission of BOE MLED, any other individual or organization is not allowed, in any form, to excerpt, reproduce, copy, translate, edit or publish this product specification. This product specification is subject to modification without prior notice.

BOE

SPEC. NUMBER	Product organization	REV.	Release date	Page
-	MLED	-	2023.11.30	2

1. Product Introduction

1.1 Scope of Application

This product specification is applicable to outdoor P6.0 full-color modules

1.2 Product Description

This product uses SMD2525 lamp beads, each of which encapsulates a red chip, a green chip, and a blue chip. The 2525 lamp beads are welded to the PCB with the surface mount technology (SMT)

This product uses a constant current driver IC chip and an integrated line driver chip and is controlled by a computer.

Lamp beads and chips are mounted on the PCB board to form a unit board, which is then mounted on the bottom case to form a module

1.3 Product Picture



2. Product Specification

Category	Parameters	Specification
Module	Pitch(mm)	6.0
	LED Model	SMD2525
	LED Type	Gold/Copper wire
	Module resolution	32*32
	Module size \pm tolerance(mm \times mm \times mm)	191.8 \pm 0.2*191.8 \pm 0.2*16.3 \pm 0.2
	Module weight \pm tolerance(g)	310 \pm 10
	Module flatness (mm)	\leq 0.55
	Pixel density (dots/m ²)	27777
Optical Parameters	White balance brightness (cd/m ²)	\geq 4500
	Color temperature	9000-15000K
	Horizontal viewing angle	\geq 120°
	Vertical viewing angle	\geq 120°
	View distance (m)	\geq 6
Electrical Parameters	Maximum power consumption per module (W)	\leq 27W
	Operating voltage (V)	5
	Signal input interface type	HUB75

SPEC. NUMBER -	Product organization MLED	REV. -	Release date 2023.11.30	Page 3
-------------------	------------------------------	-----------	----------------------------	-----------

Category	Parameters	Specification
Processing performance	Scanning mode	1/8
	Frame change frequency (Hz)	60
	Refresh frequency (Hz)	≥3840
	Driving mode	Constant drive
	Grayscale (Bit)	14
Operating Parameters	Continuous operation time	168hrs, Support uninterrupted display
	Average trouble-free working time	≥5000 hours
	Discrete runaway point	Preset at 0, < 30PPM
	Continuous runaway point	0
	Blind spot rate	Preset at 0, < 30PPM
Utilization Parameters	Typical life value (hrs)	100000
	Operating temperature (°C)	-10-60
	Storage temperature (°C)	-20-60
	Operating humidity (RH)	10%-60%
	Storage humidity (RH)	10%-60%
Protection grade	Protection grade	IP65(The protection level of the lamp surface when the back of the panel is under strict protection)
Certification	CCC	—
	Energy saving	—
	ROHS	—
	CE	—
	CB	—
	UL	—
	FCC	—

3. Definition of signal interface

HUB75		Pin	Signal	Function	Pin	Signal	Function
1	●	1	R1	Red data signal	2	G1	Green data signal
2	●	3	B1	Blue data signal	4	GND	GND of power supply
3	●	5	R2	Red data signal	6	G2	Green data signal
4	●	7	B2	Blue data signal	8	N	Suspended
5	●	9	A	Line control signal	10	B	Line control signal
6	●	11	C	Line control signal	12	N	Suspended
7	●	13	CLK	Clock signal	14	LAT	Latch signal

Copyright

The interpretation right of this product specification belongs to BOE MLED. Without the signed permission of BOE MLED, any other individual or organization is not allowed, in any form, to excerpt, reproduce, copy, translate, edit or publish this product specification. This product specification is subject to modification without prior notice.

BOE

SPEC. NUMBER -	Product organization MLED	REV. -	Release date 2023.11.30	Page 4
-------------------	------------------------------	-----------	----------------------------	-----------

	15	OE	Enable signal	16	GND	GND of power supply
--	----	----	---------------	----	-----	---------------------

4. Mounting holes

4.1 Module mounting hole location (Unit: mm)

