

Copyright

The interpretation right of this product specification belongs to BOE MLED. Without the signed permission of BOE MLED, any other individual or organization is not allowed, in any form, to excerpt, reproduce, copy, translate, edit or publish this product specification. This product specification is subject to modification without prior notice.



SPEC. NUMBER -	Product Group MLED	REV. -	Release Date 2024.11.27	Page 1
-------------------	-----------------------	-----------	----------------------------	-----------

Product Spec

BTY039B01

Rev. 1

BOE MLED Technology Co., Ltd.

Copyright

The interpretation right of this product specification belongs to BOE MLED. Without the signed permission of BOE MLED, any other individual or organization is not allowed, in any form, to excerpt, reproduce, copy, translate, edit or publish this product specification. This product specification is subject to modification without prior notice.

BOE

SPEC. NUMBER	Product Group	REV.	Release Date	Page
-	MLED	-	2024.11.27	2

1. Product Features

- 1) Lightweight, ultra-thin and high-precision die-casting aluminum panel.
- 2) The standardized cabinets are compatible with a wide range of pitches, for fast installation, and the modules are equipped with a variety of features such as anti-dust accumulation and magnetic fixation.
- 3) Widely used in indoor concerts, hotel stages and so on.

2. Product Image



Copyright

The interpretation right of this product specification belongs to BOE MLED. Without the signed permission of BOE MLED, any other individual or organization is not allowed, in any form, to excerpt, reproduce, copy, translate, edit or publish this product specification. This product specification is subject to modification without prior notice.

BOE

SPEC. NUMBER

Product Group

REV.

Release Date

Page

-

MLED

-

2024.11.27

3

3. Main Technical Parameters

Item	Technical Parameters	Item
Module Parameters	Pitch(mm)	3.906
	LED Model	SMD1515
	LED Type	Copper wire
	Module Resolution	128*64
	Scanning	1 / 16
	Module Size (mm)	499.9030.1(H)*249.9030.1(V) *5.830.2(D)
	Module Weight (kg)	1.36
	Module Flatness (mm)	≤0.2
	Pixel Density (dot/m ²)/PPI	65536
	Module Voltage (V)	DC 4.5V
Cabinet Parameters	Cabinet Composition	1*2
	Cabinet Resolution	128*128
	Cabinet Dimension (mm)	500+0/-0.15(H)*500+0/-0.15(V) * 78.830.2(D)
	Cabinet Weight (kg)	8.14
	Maintenance Mode	Front/Rear Maintenance
	Cabinet Material	Die-cast aluminum
	Cabinet Flatness (mm)	≤0.3
	Grayscale (Bit)	14Bit
	Max power consumption	780
	Average power consumption(W/m ²)	270
	Panel Voltage (V)	AC100-240V, 50/60Hz

Copyright

The interpretation right of this product specification belongs to BOE MLED. Without the signed permission of BOE MLED, any other individual or organization is not allowed, in any form, to excerpt, reproduce, copy, translate, edit or publish this product specification. This product specification is subject to modification without prior notice.



SPEC. NUMBER -	Product Group MLED	REV. -	Release Date 2024.11.27	Page 4
-------------------	-----------------------	-----------	----------------------------	-----------

	Color temperature	3000K ~ 15000K adjustable
	Viewing angle horizontal	≥160°
	Viewing angle vertical	≥110°
	White balance brightness	≥4500
	View distance (m)	≥5
Operating Parameters	Continuous operation time	≥ 7*24hrs, Support uninterrupted display
	Average trouble-free working time	≥ 10000 hrs
	Discrete runaway point	Preset at 0, 1000hrs < 3PPM
	Continuous runaway point	Preset at 0
	Blind spot rate	Preset at 0, 1000hour < 3PPM
	Screen temperature increase (operating status)	≤ 50°
Utilization Parameters	Typical life value(hrs)	100000
	Operating temperature(°C)	-20~+45
	Storage temperature(°C)	-20~+60
	Operating humidity(RH)	10%~65%PH
	Storage humidity(RH)	10%~65%PH
Protection grade	Protection grade(front/back)	IP65/IP54
Certifications	CCC	
	Energy Saving Certification	
	CE	
	CB	
	UL	
	FCC	

Copyright

The interpretation right of this product specification belongs to BOE MLED. Without the signed permission of BOE MLED, any other individual or organization is not allowed, in any form, to excerpt, reproduce, copy, translate, edit or publish this product specification. This product specification is subject to modification without prior notice.



SPEC. NUMBER -	Product Group MLED	REV. -	Release Date 2024.11.27	Page 5
-------------------	-----------------------	-----------	----------------------------	-----------

4. Diagram of panel mounting hole location

